

## TENDER DOCUMENTATION

LED LATERNA- 25W OPTICS-C; RAL7016; 3000 K

### HOUSING:

---

- Powder painted galvanised steel housing
- Gray body color (RAL7016), resistant to corrosion and brine
- Flat, tempered safety glass (optical output of LED lamp), thickness min. 4 mm
- Silicone seal around protective covers
- Stainless steel screws and washers
- Modular maintenance and repair of the luminaire is available
- Protection against water and dust: minimum IP66
- Protection against mechanical impact: minimum IK09
- Built-in valve for pressure equalization
- Maximum net weight of the light: 8,7 kg
- IP66/68 quick connector to connect the light without opening the housing

### OPTICAL CHARACTERISTICS:

---

- Road optics, full cut-off
- CCT: 3000 K
- CRI:  $\geq 70$
- Luminous efficiency of LED lamp: minimum 92 lm/W
- Minimum luminous flux of LED lamp: 2300 lm
- Drive current of LED module: maximum 500 mA
- Nominal power of LED lamp: maximum 25 W

### ELECTRICAL CHARACTERISTICS:

---

- Input voltage: 120...277 V / 50 ~ 60 Hz
- Power factor: 0.95/0.90
- Operating temperature: -20 to +45 °C
- LED driver with thermal protection and surge protection minimum 10 kV
- 5-step automatic power reduction (Astrological response)
- Long life span of LED lamp: (L80/B10)
- Electrical protection class (IEC): Class I
- Ambient temperature:  $T_a=35^{\circ}\text{C}$

### ADDITIONAL:

---

- ENEC certificate
- EU origin
- 5-year warranty on all components
- ULOR = 0